

Version: Aug 30,2017



EP-2100

POWDER COATING RESINS

TGIC

PE: HARDENER = 93:7

Description

EP-2100 is a saturated carboxylated polyester resin designed for 93/7 TGIC powders to be cured at 200°C. Coatings based on EP-2100 combine a good flow together with an excellent mechanical properties.

Specification

Item	Limits		
Acid value (mg KOH/g)	32 - 36		
Viscosity @ 200 °C, (mPa.s)	6000 - 8000		
Color, b value	Max 10		

Other

Item	Typical value	
Glass transition temperature (°C)	65	

Storage conditions

The resin in its original unopened bags is stable for more than 1 year, stored in a dry place at temperature below 30°C. Avoid direct sunlight.

Delivery form

Granules. White opaque polyethylene bags of 25kg. One ton per pallet .

Starting Formulation

Component	Weight (g)		
EP-2100	558		
TGIC	42		
TiO ₂	386		
Flow agent	10		
Benzoin	4		

Application/Extrusion Conditions

Extrusion				
Extruder		Twin screw		
Speed		250 rpm		
1st Zone Tempera	ature	95 °C		
2 nd Zone Temperature		115 °C		
Application				
Application	70 micrometer film on 0.5 mm chromated Al panel			
Spray Gun	Output voltage: 70 kV			
Curing	10 min @ 200° C metal temperature			

Coating Properties

Test Items	Result
Film thickness (microns)	60-80
Gloss @ 60° (%)	93
Cupping test (mm)	10
Direct impact (kg.cm)	80
Reverse impact (kg.cm)	80
Adhesion (grade)	0

System Properties

- Very good durable ability
- Outstanding mechanical properties
- Good over-baking resistance
- Very good flexibility properties

	Customer Service		Technical Service	
ZHEJIANG GUANGHUA TECHNOLOGY CO., LTD www.khua.com	Tel. Fax	86-573-87771555 86-573-87771222	Tel. Fax	86-573-87771188 86-573-87771222

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly or indirectly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practise any patented invention without a license.